

El-Sahel Putty 111

Ready to use putty for walls and ceilings

Description

El-Sahel Putty 111 is a high quality, vinyl copolymer-based, ready to use putty for walls and ceilings.

El-Sahel Putty 111 can be applied manually by scrapper or putty knife.

Features and benefits

- Factory prepared. Constant quality with exact mixing ratios.
- Easy to use. No mixing is required.
- Excellent workability.
- Good adhesion with minimal shrinkage.
- Can be sanded easily.
- Good whiteness.

Recommended for

El-Sahel Putty 111 is ideal for interior applications. It can be used to smooth and even out walls and ceilings variations prior to the application of emulsion and oil-based paints.

Composition

El-Sahel Putty 111 is formulated around vinyl co-polymer-based binder. It contains special types of fillers and additives.

Packaging

El-Sahel Putty 111 is available in 15 kg bags.

Coverage

0.4-0.5 kg/m²/2 coats.

Note:

Coverage rate takes no account of wastage and may vary according to surface condition and application method.

Technical data

Solid content by volume	>50%
Drying time (at 20°C and 60% relative humidity)	Touch dry: 20-30 minutes.
	Re-coat: 2 - 4 hours

Surface preparation

Cement-based plaster

Substrates to be painted should be clean, sound, and free from any contamination. Remove any traces of curing compound, laitance, organic growth or any other loose materials. Deep blowholes should be filled using **UniPutty 100**. Wash the substrate with clean water.

Coated substrates

Ensure that the existing coating is not loose. Chalked coats should be brushed down. Lightly grind the surface using very fine emery paper till the required surface is achieved. Wash the substrates with clean water and remove any excess water at the time of application.

Surface sealing

Apply one coat of **UniSeal 800** or **MagicSeal 900** to seal the prepared substrate and improve the adhesion.

Application

El-Sahel Putty 111 is ready to use putty. No mixing is required. Apply one coat of **El-Sahel Putty 111** manually using scrapper or putty knife. Allow the first coat to dry at least 2 hours minimum (according to weather conditions) prior to the application of the second coat. Final layer could be lightly grinded using very fine emery paper till the required surface is achieved.

If emulsion coat will be applied on top of **El-Sahel Putty 111**, apply one coat of **UniSeal 800** or **MagicSeal 900** before painting to improve the adhesion and increase the spreading rate of the following top coat.

Cleaning

Clean tools with water immediately after use. Hardened materials should be cleaned mechanically

Storage and shelf life

If stored unopened in a dry place at a temperature between +5°C and +30°C away from sources of heat and moisture, shelf life is 12 months from the date of manufacture printed on the pack.

Health and Safety

This is not considered dangerous according to the current regulation regarding the classification of mixtures. It should not be ingested. Wear protective gloves, eye goggles and clothing. In case of skin contact, wash with plenty of water. In case of eye contact, rinse continuously with water for several minutes and seek medical attention. Dispose excess material to special waste collection point in accordance with local & national regulation. Keep out of reach of children. For further information, please ask for Safety Data Sheet for this product.

The most up-to-date TDS can be obtained from ACC Customer Service Department, or downloaded from our website: www.acc.com.eg.

More from ACC

A wide range of construction chemicals, specialty mortars and specialized building materials are manufactured by ACC which include:

- Waterproofing.
- Flooring.
- Tile Adhesives & Grouts.
- Concrete Repair.
- Non-Shrink Grouts.
- Bonding Agents.
- Exterior Façade Coatings.
- Premixed Fairing Coats, Renders & Mortars.
- Putties (stucco).
- Sealers & Emulsion Paints.